

UPLOAD SPECIFICATIONS

NOTICE

IMPORTANT

If your artwork does not comply with these specifications, Day Print have the right to charge extra for artwork fees and/or require extra days to process the artworks.

OUTPUT

COLOUR MODE

The artwork should be saved in CMYK, Day Print will not take responsibility for any unexpected results experienced from artwork supplied in non-CMYK colours. Colour shift or errors due to incorrectly supplied files will be reprinted at the clients expense.



FILE FORMAT

- Customers must create artwork using appropriate software: Adobe Creative Suite (CS6) and Adobe PDF.
- Customers artwork must be supplied in PDF format (Multi-page files are not acceptable)



ARTWORK PROPORTION

Customers` artwork should be supplied at 1:1 scale.

Scaled artwork must be proportional with the final product.

ORIGINAL SIZE

1:1

TEXT FORMAT

- All fonts used in the artwork must be converted to outlines.
- Failure to outline fonts may cause type issues that could affect the outcome of your job.



BLEED

PDF Artwork must include bleed on all sides. Ensure bleed area is defined in PDF presets.



FILE SUPPLY METHOD

■ You may supply artwork by Email or use a file transfer service such as Wetransfer, Hightail or Google Drive.

TEMPLATES

PRODUCTS TEMPLATES

Accurate artwork templates of various products are available on our website.



SPOT UV SPECIFICATION

Artwork to be spot UV must include an individual layer of pink area in Adobe Illustrator to indicate the spot uv area.



DIE CUT

DIECUT SPECIFICATION

Artwork to be diecut must include an individual layer of pink outlines in Adobe Illustrator to indicate the die cut. (Note: Diecut outlines must be simplified for cutting, no complex shapes.)



COLOUR

INK AND COLOUR SPECIFICATIONS

- Due to CMYK printing limitation, any "Pastel" or "Spot" colour will not appear as an exact replication.
- For the best printing outcome, Rich Black (C:40%, M:40%, Y:40%, K:100%) is recommended instead of 100% Black. PMS Colour match service is available upon request. PDF Artwork must be provided with a flat PMS colour

(Gradients or transparencies cannot be colour matched)



DESIGN

ARTWORK LAYOUT SERVICE

- Artwork Design Services and artwork amendments are charged at an hourly rate, please contact your account manager or sales department for a quote.
- For more information please contact: Day: 0410 153 386 (English & Thai) or Regina: 0425 810 327 (English & Chinese)

dayprint®

UPLOAD SPECIFICATIONS

注意

重要

■ 如果您的作品不符合这些规格, Day Print有权收取额外的文稿费用和/或需要额外的 天数来处理艺术品。

文稿输出

颜色模式

■ 艺术作品应保存为CMYK颜色模式, Day Print不对非CMYK颜色模式的艺术作品所遇到 的任何结果负责。由于其他的颜色模式导致的色移或错误将于客户费用重新打印。



文件格式

- 客户必须使用适当的软件创建文稿: Adobe Creative Suite CS6和Adobe PDF。
- 客户图稿必须以PDF格式提供(不接受多页文件)



文稿比例

- 客户的文稿应以1:1的比例提供。
- 提供的缩放的图稿必须与最终产品成比例。

ORIGINAL SIZE

1:1

文字格式

- 必须将图稿中使用的所有字体转换为轮廓。
- 确保轮廓输出的正确性,因为如果出现无法认读的轮廓会导致影响成品结果的问题。



出血

■ PDF艺术品必须包括四周的出血。确保在PDF预设中定义出血区域。



文件的提供方法

■ 您可以通过电子邮件提供艺术作品或使用Wetransfer, Hightail或Google Drive等文件传输服务。

模板

产品模板

■ 我们的网站上提供各种产品的精确图稿模板。

局部UV

局部UV规格

- 作为UV点的图稿必须包含单独的粉红色区域图层,以指示局部UV。



模切

模切规格

■要进行模切的图稿必须包含单独的粉红色轮廓图层,以指示模切。(注意:切割时必须简化模切轮廓,没有复杂的形状。)



颜色

油墨和颜色规格

- 由于CMYK打印限制,任何"Pastel"或"Spot"颜色都会不会显示为完全复制。 为了获得最佳印刷效果,建议使用全黑(C:40% M:40% Y:40% K:100%)而不是 单色黑(K:100%)。
- PMS色彩匹配服务可根据要求提供。PDF艺术品必须提供平坦的PMS颜色 (渐变或透明胶片不能匹配颜色)



设计

文稿设计服务

- 文稿设计和修改服务是收费的,按小时计算,请联系我们报价。
- 详情请联系:

Day: 0410 153 386 (英文和泰文)或 Regina: 0425 810 327 (中文和英文)